

DIN-Signal coax m, solder/crimp 500hm



Part number	09 03 000 6165
Specification	DIN-Signal coax m, solder/crimp 500hm
HARTING eCatalogue	https://b2b.harting.com/09030006165

Image is for illustration purposes only. Please refer to product description.

Identification

Category	Contacts
Type of contact	Coaxial contact
Description of the contact	Straight
Contacts for	DIN 41612 Type M DIN 41612 Bauform M 0+2
Version	
Termination method	PCB solder termination
Gender	Male contact for female connectors
Manufacturing process	Turned contacts
Performance level	1
Technical characteristics	
Impedance	50 Ω
Material properties	
Material (contacts)	Copper alloy
Surface (contacts)	Noble metal
RoHS	compliant with exemption
RoHS exemptions	6(c): Copper alloy containing up to 4 % lead by weight
ELV status	compliant with exemption
China RoHS	50
REACH Annex XVII substances	No

Page 1 / 2 | Creation date 2020-08-21 | Please note that the data specified here were taken as extracts from the online catalogue. Please refer to the user documentation for the complete and up-to-date information and data. Please also note that the user is responsible for validating functionality, conformity with applicable laws and directives, as well as for the electrical safety in the particular application. HARTING Electronics GmbH | Marienwerderstraße 3 | 32339 Espelkamp | Germany Phone +49 5772 47-97200 | electronics@HARTING.com | www.HARTING.com



Material properties	
REACH ANNEX XIV substances	No
REACH SVHC substances	Yes
REACH SVHC substances	Lead
Specifications and approvals	
Specifications	DIN 41626
Commercial data	
Packaging size	100
Net weight	1.43 g
Country of origin	Germany
European customs tariff number	85366990
eCl@ss	27440204 Contact for industrial connectors