


# SEK 17-14(2)M-S32-AU KONTAKT 1



Part number	09 17 014 9622
Specification	SEK 17-14(2)M-S32-AU KONTAKT 1
HARTING eCatalogue	https://b2b.harting.com/09170149622

Image is for illustration purposes only. Please refer to product description.

## Identification

Category	Connectors
Series	SEK
Element	DIP connector
Description of the contact	Straight

#### Version

Connection type	PCB to cable
Number of contacts	14
Details	for IDC flat cable 1.27 mm (0.050") pitch AWG 28/7

#### Technical characteristics

Contact rows	2
Contact spacing (termination side)	2.54 mm
Contact spacing (mating side)	1.27 mm
Rated current	1 A
Insulation resistance	>10 <sup>12</sup> Ω
Contact resistance	≤20 mΩ
Limiting temperature	-40 +125 °C
Test voltage U <sub>r.m.s.</sub>	0.5 kV

## Material properties

Material (insert) Thermoplastic resin (PC)
--



## Material properties

Colour (insert)	Beige
Material flammability class acc. to UL 94	V-0
RoHS	compliant
ELV status	compliant
China RoHS	е
REACH Annex XVII substances	No
REACH ANNEX XIV substances	No
REACH SVHC substances	No

# Specifications and approvals

Specifications	IEC 60603-13
Openications	120 00000 10

## Commercial data

Packaging size	130
Net weight	3.92 g
Country of origin	Germany
European customs tariff number	85366990
eCl@ss	27440309 Cable connector for printed circuit board