



Pushing Performance

R 15-GG mit M16



| | |
|--------------------|---|
| Part number | 19 15 000 0401 |
| Specification | R 15-GG mit M16 |
| HARTING eCatalogue | https://b2b.harting.com/19150000401 |

Identification

| | |
|--------------------------|----------------|
| Category | Hoods/Housings |
| Series of hoods/housings | R 15 |
| Type of hood/housing | Hood |

Version

| | |
|--------------|---------------|
| Locking type | Screw locking |
| Cable entry | 1x M16 |

Technical characteristics

| | |
|--|-----------------|
| Limiting temperature | -40 ... +125 °C |
| Degree of protection acc. to IEC 60529 | IP65 |

Material properties

| | |
|-----------------------------|--------------------|
| Material (hood/housing) | Polycarbonate (PC) |
| RoHS | compliant |
| ELV status | compliant |
| China RoHS | e |
| REACH Annex XVII substances | No |
| REACH ANNEX XIV substances | No |
| REACH SVHC substances | No |

Commercial data

| | |
|----------------|---------|
| Packaging size | 10 |
| Net weight | 16.28 g |



Pushing Performance

Commercial data

| | |
|--------------------------------|--|
| Country of origin | Germany |
| European customs tariff number | 85389099 |
| eCl@ss | 27440224 Shell for circular connectors |