

## Han 3A-SIS-SL-M20



Image is for illustration purposes only. Please refer to product description.

|                    |   |
|--------------------|---|
| Part number        | 19 20 003 1150  |
| Specification      | Han 3A-SIS-SL-M20   |
| HARTING eCatalogue | <a href="https://b2b.harting.com/19200031150">https://b2b.harting.com/19200031150</a> |

### Identification

|                          |                       |
|--------------------------|-----------------------|
| Category                 | Hoods/Housings        |
| Series of hoods/housings | Han A <sup>®</sup>    |
| Type of hood/housing     | Screw mounted housing |

### Version

|                      |   |
|----------------------|---|
| Locking type         | Single locking lever                                |
| Size                 | 3 A   |
| Cable entry          | 1x M20  |
| Field of application | Standard Hoods/housings for industrial applications |

### Technical characteristics

|  |  |
|--|--|
| Limiting temperature                   | -40 ... +125 °C                                    |
| Degree of protection acc. to IEC 60529 | IP44<br>IP65 / IP67 with seal screw 09 20 000 9918 |
| Type rating acc. to UL 50 / UL 50E     | 12   |

### Material properties

|                         |                          |
|-------------------------|--------------------------|
| Material (hood/housing) | Zinc die-cast            |
| Surface (hood/housing)  | Powder-coated            |
| Colour (hood/housing)   | RAL 7037 (dust grey)     |
| Material (locking)      | Steel                    |
| Surface (locking)       | Zinc plated              |
| RoHS                    | compliant with exemption |



Pushing Performance

## Material properties

|                             |   |
|-----------------------------|---|
| RoHS exemptions             | 6(a) / 6(a)-I: Lead as an alloying element in steel for machining purposes and in galvanised steel containing up to 0,35 % lead by weight / Lead as an alloying element in steel for machining purposes containing up to 0,35 % lead by weight and in batch hot dip galvanised steel components containing up to 0,2 % lead by weight<br>6(c): Copper alloy containing up to 4 % lead by weight |
| ELV status                  | compliant with exemption  |
| China RoHS                  | 50  |
| REACH Annex XVII substances | No  |
| REACH ANNEX XIV substances  | No  |
| REACH SVHC substances       | Yes   |
| REACH SVHC substances       | Lead  |

## Specifications and approvals

|           |        |
|-----------|--------|
| Approvals | DNV GL |
|-----------|--------|

## Commercial data

|                                |  |
|--------------------------------|--|
| Packaging size                 | 10                                       |
| Net weight                     | 57.71 g                                  |
| Country of origin              | Germany                                  |
| European customs tariff number | 85389099                                 |
| eCl@ss                         | 27440202 Shell for industrial connectors |