



F	Part number	19 30 024 0538
ę	Specification	Han B Hood Side Entry HC 2 Levers M40
ŀ	HARTING eCatalogue	https://b2b.harting.com/19300240538

Han B Hood Side Entry HC 2 Levers M40

Image is for illustration purposes only. Please refer to product description.

Identification

Category	Hoods/Housings
Series of hoods/housings	Han [®] B
Type of hood/housing	Hood
Туре	High construction

Version

Locking type	Double locking lever (on the hood)
Han-Easy Lock [®]	Yes
Size	24 B
Version	Side entry
Cable entry	1x M40
Field of application	Standard hoods/housings for industrial connectors

Technical characteristics

Limiting temperature	-40 +125 °C
Degree of protection acc. to IEC 60529	IP65
	4
Type rating acc. to UL 50 / UL 50E	4X
	12

Material properties

Material (hood/housing)	Aluminium die-cast
Surface (hood/housing)	Powder-coated
Colour (hood/housing)	RAL 7037 (dust grey)

Page 1 / 2 | Creation date 2019-12-06 | Please note that the data specified here were taken as extracts from the online catalogue. Please refer to the user documentation for the complete and up-to-date information and data. Please also note that the user is responsible for validating functionality, conformity with applicable laws and directives, as well as for the electrical safety in the particular application. HARTING Electric GmbH & Co. KG | Wilhelm-Harting-Straße 1 | 32339 Espelkamp | Germany Phone +49 5772 47-97100 | electric@HARTING.com | www.HARTING.com



Material properties

Material (locking)	Polycarbonate (PC) Stainless steel		
Colour (locking)	RAL 7037 (dust grey)		
Material flammability class acc. to UL 94 (locking levers)	V-0		
RoHS	compliant		
ELV status	compliant		
China RoHS	e		
REACH Annex XVII substances	No		
REACH ANNEX XIV substances	No		
REACH SVHC substances	No		
Specifications and approvals			
Approvals	DNV GL		
Commercial data			
Packaging size	1		
Net weight	279 g		
Country of origin	Germany		
European customs tariff number	85389099		
eCl@ss	27440202 Shell for industrial connectors		