

## Han 10HvE-kg-QB-M32



Image is for illustration purposes only. Please refer to product description.

Part number	19 34 010 0732
Specification	Han 10HvE-kg-QB-M32
HARTING eCatalogue	<a href="https://b2b.harting.com/19340100732">https://b2b.harting.com/19340100732</a>

### Identification

Category	Hoods/Housings
Series of hoods/housings	Han Hv E <sup>®</sup>
Type of hood/housing	Cable to cable housing
Type	Low construction

### Version

Locking type	Double locking lever
Han-Easy Lock <sup>®</sup>	Yes
Size	24 B
Version	Top entry
Cable entry	1x M32
Field of application	Special hoods/housings for Han Hv E <sup>®</sup> screw terminal

### Technical characteristics

Limiting temperature	-40 ... +125 °C
Degree of protection acc. to IEC 60529	IP65
Type rating acc. to UL 50 / UL 50E	4 4X 12

### Material properties

Material (hood/housing)	Aluminium die-cast
Surface (hood/housing)	Powder-coated



Pushing Performance

## Material properties

Colour (hood/housing)	RAL 7037 (dust grey)
Material (seal)	NBR
Material (locking)	Polycarbonate (PC) Stainless steel
Colour (locking)	RAL 7037 (dust grey)
Material flammability class acc. to UL 94 (locking levers)	V-0
RoHS	compliant
ELV status	compliant
China RoHS	e
REACH Annex XVII substances	No
REACH ANNEX XIV substances	No
REACH SVHC substances	No

## Specifications and approvals

Approvals	DNV GL
-----------	--------

## Commercial data

Packaging size	1
Net weight	252.3 g
Country of origin	Germany
European customs tariff number	85389099
eCl@ss	27440202 Shell for industrial connectors