

Han 24HPR Hood Top Entry 2xM40 Screw loc



Image is for illustration purposes only. Please refer to product description.

| | |
|--------------------|---------------------------------------------------------------------------------------|
| Part number | 19 40 024 0438 |
| Specification | Han 24HPR Hood Top Entry 2xM40 Screw loc |
| HARTING eCatalogue | https://b2b.harting.com/19400240438 |

Identification

| | |
|-----------------------------|----------------------|
| Category | Hoods/Housings |
| Series of hoods/housings | Han [®] HPR |
| Type of hood/housing | Hood |
| Description of hood/housing | With adapter |

Version

| | |
|----------------------|-----------------------------------------------|
| Locking type | Screw locking |
| Size | 24 B |
| Version | Top entry |
| Cable entry | 2x M40 |
| Field of application | Hoods/housings for harsh outdoor environments |

Technical characteristics

| | |
|----------------------------------------|------------------------------------------------|
| Limiting temperature | -40 ... +125 °C |
| Tightening torque (screw locking) | 4 Nm |
| Degree of protection acc. to IEC 60529 | IP65 IP68 IP69 / IPX9K acc. to ISO 20653 |
| Type rating acc. to UL 50 / UL 50E | 4 4X 12 |

Material properties

| | |
|-------------------------|-------------------------------------------|
| Material (hood/housing) | Aluminium die-cast Corrosion resistant |
|-------------------------|-------------------------------------------|



Pushing Performance

Material properties

| | |
|-----------------------------|--------------------------------------------------------|
| Surface (hood/housing) | Powder-coated |
| Colour (hood/housing) | RAL 9005 (jet black) |
| Material (locking) | Stainless steel |
| RoHS | compliant with exemption |
| RoHS exemptions | 6(c): Copper alloy containing up to 4 % lead by weight |
| ELV status | compliant with exemption |
| China RoHS | 50 |
| REACH Annex XVII substances | No |
| REACH ANNEX XIV substances | No |
| REACH SVHC substances | Yes |
| REACH SVHC substances | Lead |

Specifications and approvals

| | |
|-----------|------------------------------------------------------------|
| Approvals | DNV GL |
| UL / CSA | UL 1977 ECBT2.E235076 CSA-C22.2 No. 182.3 ECBT8.E235076 |

Commercial data

| | |
|--------------------------------|------------------------------------------|
| Packaging size | 1 |
| Net weight | 920.5 g |
| Country of origin | Germany |
| European customs tariff number | 85389099 |
| eCl@ss | 27440202 Shell for industrial connectors |